

GRINDING & SANDING

Pneumatic Grinder

MYTON

Heavy-duty grinders for tough applications

- Side exhaust with noise reduction system
- Great power/weight ratio

NEW

Model MYG-25L

- For Grinding Wheel 58 mm
- Compact and lightweight type



 YouTube



NEW

Model MYG-40L

- For Grinding Wheel 100 mm
- Powerful type



 YouTube



Model MG-40

- Lever switch type
- Depressed center wheel 100 mm



 YouTube



Model MG-40 Non-CE

- Ring switch type
- Depressed center wheel 100 mm



Specifications

Model	MYG-25L	MYG-40L	MG-40 Lever Type	MG-40 Ring Type
Air Pressure	MPa (kgf/cm ²)	0.6 (6)		
Air Consumption	m ³ /min	0.39 (No-load)	0.54 (No-load) 0.75 (Load)	0.50 (No-load)
Free Speed	min ⁻¹ (rpm)	19000	13000	
Depressed Center Grinding Wheel Outer Diameter	mm	58	100	
Air Inlet Size	kg	Rc 1/4	Rc 3/8	Rc 1/4
Mass (Weight)		0.6	1.55	1.6
Accessories Included	<ul style="list-style-type: none"> • 5 mm Hex. Socket Screw Key • Spanner 19 • Grinding Wheel GS #80 x 58 • Bushing R 1/4 x NPT 1/4 	<ul style="list-style-type: none"> • 5 mm Hex. Socket Screw Key • 6 mm Hex. Socket Screw Key • Bushing R 3/8 x NPT 3/8 	<ul style="list-style-type: none"> • 5 mm Hex. Socket Screw Key • 6 mm Hex. Socket Screw Key • Spanner 19 • Bushing R 3/8 x NPT 3/8 	<ul style="list-style-type: none"> • 5 mm Hex. Socket Screw Key • 6 mm Hex. Socket Screw Key • Spanner 19 • Bushing R 1/4 x NPT 3/8

Model MYG-50

- Lever switch type
- For Grinding wheel 125 mm
- Heavy grinding type
- Anti-vibration handle



 YouTube



Model MYG-70

- Lever switch type
- For Grinding wheel 180 mm
- Heavy grinding type



Model MYG-70 Non-CE

- Ring switch type
- For Grinding wheel 180 mm
- Heavy grinding type



Specifications

Model	MYG-50	MYG-70 Lever Type	MYG-70 Ring Type
Air Pressure	MPa (kgf/cm ²)	0.6 (6)	
Air Consumption	m ³ /min	0.75 (No-load) 1.1 (Load)	0.70 (No-load) 0.95 (Load)
Free Speed	min ⁻¹ (rpm)	11000	7600
Depressed Center Grinding Wheel Outer Diameter	mm	125	180
Air Inlet Size	kg	Rc 3/8	
Mass (Weight)		2.5 (with handle)	2.4 (with handle)
Accessories Included	<ul style="list-style-type: none"> • Handle (anti-vibration type) • 4 mm Hex. Socket Screw Key • 6 mm Hex. Socket Screw Key • Pin Face Wrench • Bushing R 3/8 x NPT 3/8 	<ul style="list-style-type: none"> • Handle • 6 mm Hex. Socket Screw Key • 10 mm Hex. Socket Screw Key • Bushing R 3/8 x NPT 3/8 	